



## Husqvarna ELITE-CUT F635

The Husqvarna F 635 is a blade for cured concrete with medium-hard (granite) to hard (quartz) aggregate. The Husqvarna F 640 is a blade for cured concrete with soft (limestone) to medium (granite) aggregate.

### **Sandwich segment design**

Helps the blade to retain the shape ensuring superior cutting speed and maximum utilisation of the full segment height.

### **Wide application window**

Designed to cover a wide window of applications with a very good performance.

### **Long life**

To tackle the high power of the machine, the blade (most diameters) are equipped with narrow water slots that give a wider segment, longer service and increased life.

### **Possible to customise**

This extensive series covers most applications, and customised tools can be arranged upon request.

## FEATURES

- To tackle the high power of the machine, the blade (most diameters) are equipped with narrow water slots that give a wider segment, longer service and increased life.
- Designed to cover a wide window of applications with a very good performance.
- Helps the blade to retain the shape ensuring superior cutting speed and maximum utilisation of the full segment height.
- This extensive series covers most applications, and customised tools can be arranged upon request.
- Segments are attached to the tube by laser welding to minimise the risk of segment loss.

### Technical Specifications

#### GENERAL

Article Description	450N 3.6 25.4 F635
Performance grade	Gold
Blade configuration	Narrow slots
Coolant	Wet
Power range, max kW	53.69 kW
Power range, min kW	14.91 kW

#### DIMENSIONS

Diameter mm	450 mm
Arbor diameter	25.4 mm
Segment height mm	10 mm
Segment length mm	40 mm
Segment width mm	3.2 mm
Article gross weight	3989 g
Article net weight	3639 g

#### MATERIALS

Brick	Good
Cured concrete hard	Optimal
Cured concrete medium	Good
Cured concrete soft	Acceptable
Reinforced concrete	Good

#### PACKAGING

Packaging length	468 mm
Packaging width	468 mm
Packaging height	20 mm