

Husqvarna W1525

Efficient cooling

The notch design of the segments provides efficient cooling of the blade, and evacuates the abrasive slurry.

Sandwich segment design

Helps the blade to retain the shape ensuring superior cutting speed and maximum utilisation of the full segment height.

Wide application window

Designed to cover a wide window of applications with a very good performance.

FEATURES

- Designed to cover a wide window of applications with a very good performance.
- Helps the blade to retain the shape ensuring superior cutting speed
- and maximum utilisation of the full segment height.
- The notch design of the segments provides efficient cooling of the blade, and evacuates the abrasive slurry.

echnical Specifications	
GENERAL	
Article Description	1200W 4.5 60.0 W1525 PL3012
Performance grade	Gold
Blade configuration	Segmented
Coolant	Wet
Arbor hole pattern	PL3012
Power range, max kW	20 kW
Power range, min kW	15 kW
DIMENSIONS	
Diameter mm	1200 mm
Arbor diameter	60 mm
Segment height mm	14 mm
Segment length mm	40 mm
Segment width mm	4.5 mm
Article gross weight	50944 g
Article net weight	30944 g
MATERIALS	
Brick	Good
Concrete medium	Good
Highly reinforced concrete	Optimal
Reinforced concrete	Optimal
PACKAGING	
Packaging length	1230 mm
Packaging width	1230 mm
Packaging height	25 mm